



(12) **United States Patent**
Darr et al.

(10) **Patent No.:** **US 10,214,312 B2**
(45) **Date of Patent:** **Feb. 26, 2019**

(54) **LIGHTWEIGHT PLASTIC CONTAINER AND PREFORM**

(71) Applicant: **Plastipak Packaging, Inc.**, Plymouth, MI (US)

(72) Inventors: **Richard C. Darr**, Medina, OH (US);
Edward V. Morgan, Northville, MI (US)

(73) Assignee: **Plastipak Packaging, Inc.**, Plymouth, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/013,196**

(22) Filed: **Jun. 20, 2018**

(65) **Prior Publication Data**
US 2018/0297740 A1 Oct. 18, 2018

Related U.S. Application Data
(60) Continuation of application No. 16/012,302, filed on Jun. 19, 2018, which is a continuation of application (Continued)

(51) **Int. Cl.**
B65D 1/02 (2006.01)
B29B 11/08 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B65D 1/0246** (2013.01); **B29B 11/08** (2013.01); **B29B 11/14** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B65D 1/0246; B65D 1/023; B65D 1/40; B65D 1/0284; B65D 1/0207; B65D 1/46;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,367,317 A * 1/1945 Thomas B65D 41/348 215/252
3,398,427 A 8/1968 John
(Continued)

FOREIGN PATENT DOCUMENTS

DE 202005017075 U1 2/2006
EP 0316167 A2 5/1989
(Continued)

OTHER PUBLICATIONS

Brandau, Ottmar, Ed., Bottles, Preforms, Closures—A Design Guide for PET Packaging, 2005, pp. 142-143, Print vol. 4, PETplanet Publisher, Heidelberg, Germany [ISBN 3-9807497-3-8].

(Continued)


Primary Examiner — Karen K Thomas

(74) *Attorney, Agent, or Firm* — Fishman Stewart PLLC

(57) **ABSTRACT**

A plastic container is provided that includes a hollow body portion including a lower supporting base portion; a sidewall portion extending upwardly from the base portion; and a neck portion extending upwardly from the sidewall portion. The neck portion includes a support flange having an upper and lower surface, a tamper-evident formation, and a dispensing opening at the top of the neck portion. In embodiments, a closure may be provided to form an assembly. In embodiments, the container is comprised of polyethylene terephthalate (PET), a volume of the container is at least 500 ml, and/or the weight of the neck portion is 2.3 grams or less. A preform and method for making a container are also disclosed.

30 Claims, 3 Drawing Sheets



Related U.S. Application Data

No. 15/495,084, filed on Apr. 24, 2017, now Pat. No. 10,023,345, which is a continuation of application No. 15/404,731, filed on Jan. 12, 2017, now Pat. No. 9,738,409, which is a continuation of application No. 15/383,179, filed on Dec. 19, 2016, now Pat. No. 9,850,019, which is a continuation of application No. 15/220,731, filed on Jul. 27, 2016, now Pat. No. 9,522,759, which is a continuation of application No. 14/803,505, filed on Jul. 20, 2015, now Pat. No. 9,403,310, which is a continuation of application No. 14/688,734, filed on Apr. 16, 2015, now Pat. No. 9,139,326, which is a continuation of application No. 14/511,848, filed on Oct. 10, 2014, now Pat. No. 9,033,168, which is a division of application No. 11/749,501, filed on May 16, 2007, now Pat. No. 8,857,637, which is a continuation-in-part of application No. 11/368,860, filed on Mar. 6, 2006, now Pat. No. 7,708,159.

2911/14746; B29B 2911/14726; B29B 2911/14686; B29B 2911/14666; B29B 2911/14626; B29B 2911/146; B29B 2911/14466; B29B 2911/14444; B29B 2911/14333; B29B 2911/14326; B29L 2031/7158; Y10T 428/1397; Y10T 428/1352; B29K 2067/003; B29K 2105/26; B29K 2105/258; B29K 2067/00

USPC 215/40, 42, 44, 252; 220/640, 643, 645, 220/656, 657, 659

See application file for complete search history.

(51) **Int. Cl.**

B29B 11/14 (2006.01)
B29C 49/00 (2006.01)
B29C 47/00 (2006.01)
B65D 43/02 (2006.01)
B65D 1/44 (2006.01)
B65D 1/46 (2006.01)
B29C 49/06 (2006.01)
B29C 49/08 (2006.01)
B65D 1/40 (2006.01)
B29K 67/00 (2006.01)
B29K 105/00 (2006.01)
B29K 105/26 (2006.01)
B29L 31/00 (2006.01)
B29C 49/46 (2006.01)

(52) **U.S. Cl.**

CPC **B29C 47/0073** (2013.01); **B29C 49/0073** (2013.01); **B29C 49/0078** (2013.01); **B29C 49/06** (2013.01); **B29C 49/08** (2013.01); **B65D 1/023** (2013.01); **B65D 1/0207** (2013.01); **B65D 1/0284** (2013.01); **B65D 1/40** (2013.01); **B65D 1/44** (2013.01); **B65D 1/46** (2013.01); **B65D 43/0235** (2013.01); **B29B 2911/146** (2013.01); **B29B 2911/1444** (2013.01); **B29B 2911/1466** (2013.01); **B29B 2911/1498** (2013.01); **B29B 2911/14326** (2013.01); **B29B 2911/14333** (2013.01); **B29B 2911/14446** (2013.01); **B29B 2911/14466** (2013.01); **B29B 2911/14626** (2013.01); **B29B 2911/14666** (2013.01); **B29B 2911/14686** (2013.01); **B29B 2911/14713** (2013.01); **B29B 2911/14726** (2013.01); **B29B 2911/14746** (2013.01); **B29C 49/46** (2013.01); **B29C 2049/4664** (2013.01); **B29K 2067/00** (2013.01); **B29K 2067/003** (2013.01); **B29K 2105/258** (2013.01); **B29K 2105/26** (2013.01); **B29L 2031/7158** (2013.01); **Y10T 428/1352** (2015.01); **Y10T 428/1397** (2015.01)

(58) **Field of Classification Search**

CPC **B65D 1/44**; **B65D 43/0235**; **B29C 49/08**; **B29C 49/06**; **B29C 49/0078**; **B29C 47/0073**; **B29C 49/0073**; **B29C 2049/4664**; **B29C 49/46**; **B29B 11/14**; **B29B 11/08**; **B29B 2911/1466**; **B29B 2911/14713**; **B29B 2911/1498**; **B29B**

(56)

References Cited

U.S. PATENT DOCUMENTS

3,559,833 A	2/1971	Alonso	
3,881,622 A	5/1975	Dockery	
4,098,419 A	7/1978	Virog, Jr. et al.	
4,177,906 A	12/1979	Von Hagel	
4,180,175 A	12/1979	Virog, Jr. et al.	
4,301,937 A	11/1981	Von Hagel	
4,342,398 A	8/1982	Chang	
4,401,227 A	8/1983	Pehr	
4,463,056 A	7/1984	Steele	
4,541,536 A	9/1985	Davis et al.	
4,615,667 A	10/1986	Roy	
4,715,504 A	12/1987	Chang et al.	
4,756,438 A	7/1988	Ryder	
4,830,251 A	5/1989	Conrad	
4,842,153 A	6/1989	Hulon	
5,040,692 A	8/1991	Julian	
5,104,704 A *	4/1992	Labes	B65D 55/06 206/459.1
5,143,235 A	9/1992	Repp	
5,366,774 A	11/1994	Pinto	
5,403,538 A	4/1995	Maeda	
5,464,106 A	11/1995	Slat et al.	
5,645,183 A	7/1997	Slat	
5,647,495 A	7/1997	Orimoto et al.	
5,674,448 A	10/1997	Slat et al.	
5,676,267 A	10/1997	Stat	
5,688,572 A	11/1997	Slat et al.	
5,756,172 A	5/1998	Semersky	
5,804,305 A	9/1998	Slat et al.	
5,888,598 A *	3/1999	Brewster	B29C 49/0005 264/513
5,918,753 A	7/1999	Ogg et al.	
5,927,525 A	7/1999	Darr et al.	
5,954,216 A	9/1999	Meisner et al.	
5,975,320 A	11/1999	Bietzer et al.	
6,041,953 A	3/2000	Goodall	
6,063,325 A	5/2000	Nahill et al.	
6,082,568 A	7/2000	Flanagan	
6,085,924 A	7/2000	Henderson	
6,168,749 B1	1/2001	Koch	
6,203,870 B1	3/2001	Darr	
6,276,546 B1	8/2001	Davis et al.	
6,305,564 B1	10/2001	Takeuchi et al.	
6,391,408 B1	5/2002	Hutchinson	
6,461,697 B1	10/2002	Slat et al.	
6,548,133 B2	4/2003	Schmidt et al.	
6,557,714 B2	5/2003	Babcock et al.	
6,568,156 B2	5/2003	Silvers et al.	
6,635,325 B1	10/2003	Hebert	
6,641,774 B2	11/2003	Slat et al.	
6,673,303 B2	1/2004	White et al.	
6,779,677 B2	8/2004	Chupak	
6,796,450 B2	9/2004	Prevot et al.	
6,808,820 B2	10/2004	Lee et al.	
6,837,390 B2	1/2005	Lane et al.	
6,841,262 B1	1/2005	Beck et al.	
6,854,614 B2	2/2005	Sprick	
6,929,139 B2	8/2005	Darr	
6,939,591 B2	9/2005	Hutchinson et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

6,971,530	B2	12/2005	Darr
6,977,104	B1	12/2005	Nahill et al.
6,991,336	B2	1/2006	Matsui
7,080,747	B2	7/2006	Lane et al.
7,150,902	B2	12/2006	Farha
7,332,204	B2	2/2008	Hutchinson et al.
7,531,226	B2	5/2009	Lee et al.
7,553,441	B2	6/2009	Shi
7,882,977	B2	2/2011	Johnson
7,976,767	B2	7/2011	Ungrady
8,308,005	B2	11/2012	Penny
2001/0038171	A1	11/2001	Darr
2001/0054779	A1	12/2001	Collette et al.
2002/0022099	A1	2/2002	Schmidt et al.
2002/0134747	A1	9/2002	Babcock et al.
2002/0162818	A1	11/2002	Williams
2003/0041568	A1	3/2003	Seidita
2003/0071007	A1	4/2003	Ma et al.
2003/0116522	A1	6/2003	Julian et al.
2003/0155320	A1	8/2003	Peronek et al.
2003/0235667	A1	12/2003	Darr et al.
2004/0084333	A1	5/2004	Boyd
2004/0091651	A1	5/2004	Rule et al.
2004/0129669	A1	7/2004	Kelley et al.
2004/0146675	A1	7/2004	Hashimoto et al.
2005/0053739	A1	3/2005	Lee et al.
2005/0139566	A1	6/2005	Uesugi et al.
2005/0153089	A1	7/2005	Lynch et al.
2005/0158495	A1	7/2005	Nahill
2005/0167879	A1	8/2005	Smith
2005/0258127	A1	11/2005	Darr
2006/0105127	A1	5/2006	Akiyama et al.
2006/0121222	A1	6/2006	Andrich et al.
2006/0207961	A1	9/2006	Kurtz

2007/0087214	A1	4/2007	Portnoy et al.
2007/0108668	A1	5/2007	Hutchinson et al.
2007/0175855	A1	8/2007	Penny
2007/0224374	A1	9/2007	Kelley
2007/0257001	A1	11/2007	Paz
2008/0050546	A1	2/2008	Kitano et al.
2008/0290099	A1	11/2008	MacDonald et al.

FOREIGN PATENT DOCUMENTS

EP	1633639	A1	3/2006
EP	1714887	A1	10/2006
EP	1885602	B1	10/2010
FR	2846946	A1	5/2004
JP	59-184627		10/1984
JP	2002240136	A	8/2002
JP	20051383	A	1/2005
JP	2007039109	A	2/2007
WO	9829314	A1	7/1998
WO	9961325	A2	12/1999
WO	9961337	A2	12/1999
WO	2004065105	A1	8/2004
WO	2006/066356	A1	6/2006

OTHER PUBLICATIONS

PCT/US07/01880 International Search Report and Written Opinion dated Nov. 19, 2007.
 Extended Search Report issued in European Patent Application No. 08755571 dated Jan. 7, 2011.
 PCT/US08/63744 International search report and written opinion dated Sep. 2, 2008.
 ASTM Standard Specification for Dimensions and Tolerances for Plastic Bottles.
 ISBT nomenclature.

* cited by examiner




FIG 1




FIG 2




FIG 3




FIG 4




FIG 5




FIG 6

LIGHTWEIGHT PLASTIC CONTAINER AND PREFORM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/012,302, filed Jun. 19, 2018, which is a continuation of U.S. patent application Ser. No. 15/495,084, filed Apr. 24, 2017, which is a continuation of U.S. patent application Ser. No. 15/404,731, filed Jan. 12, 2017, now U.S. Pat. No. 9,738,409, which is a continuation of U.S. patent application Ser. No. 15/383,179, filed Dec. 19, 2016, now U.S. Pat. No. 9,850,019, which is a continuation of U.S. patent application Ser. No. 15/220,731, filed Jul. 27, 2016, now U.S. Pat. No. 9,522,759, which is a continuation of U.S. patent application Ser. No. 14/803,505, filed Jul. 20, 2015, now U.S. Pat. No. 9,403,310, which is a continuation of U.S. patent application Ser. No. 14/688,734, filed Apr. 16, 2015, now U.S. Pat. No. 9,139,326, which is a continuation of U.S. patent application Ser. No. 14/511,848, filed Oct. 10, 2014, now U.S. Pat. No. 9,033,168, which is a divisional of U.S. patent application Ser. No. 11/749,501, filed May 16, 2007, now U.S. Pat. No. 8,857,637, which is a continuation-in-part of U.S. patent application Ser. No. 11/368,860, filed Mar. 6, 2006, now U.S. Pat. No. 7,708,159, all of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

The present invention relates to plastic containers, including injection molded and/or blow molded containers.

BACKGROUND

It is desirable to improve the stability of plastic containers and the handling of preforms that are used to form containers. At the same time, for economic and efficiency reasons, it is also desirable to provide containers and preforms that are suitable for their intended applications yet have a reduced weight.

SUMMARY

A plastic container is provided that includes a hollow body portion including a lower supporting base portion; a sidewall portion extending upwardly from the base portion; and a neck portion extending upwardly from the sidewall portion. The neck portion includes a support flange having an upper and lower surface, a tamper-evident formation, and a dispensing opening at the top of the neck portion. In embodiments, a closure may be provided to form an assembly. In embodiments, the container is comprised of polyethylene terephthalate (PET), a volume of the container is at least 500 ml, and/or the weight of the neck portion is 2.3 grams or less. A preform and method for making a container are also disclosed.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the invention will now be described, by way of example, with reference to the accompanying drawings, wherein:

FIG. 1 is a front elevational view of a plastic container according to an embodiment of the invention.

FIG. 2 is a front elevation view of a preform according to another embodiment of the invention.

FIG. 3 is a cross-sectional view of a preform according to an embodiment of the invention.

FIG. 4 is a partial enlarged view of the area illustrated in FIG. 2.

FIG. 5 is a partial cross sectional view of an upper portion of a container or preform according to an embodiment of the invention.

FIG. 6 is a perspective view of a neck portion of a container or preform according to an embodiment of the invention.

DETAILED DESCRIPTION

Reference will now be made in detail to embodiments of the present invention, examples of which are described herein and illustrated in the accompanying drawings. While the invention will be described in conjunction with embodiments, it will be understood that they are not intended to limit the invention to these embodiments. On the contrary, the invention is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the invention as defined by the appended claims.

A representative container **10** according to an embodiment of the present invention is generally shown in FIG. 1. Container **10** includes a lower supporting base portion **12**, a sidewall portion **14**, and a neck portion **16**.

The sidewall portion may be cylindrical or non-cylindrical, and may include various formations, for example, without limitation, label panels, strengthening ribs, etc. The neck portion **16** includes a support flange **18** having an upper surface **20** and a lower surface **22**. Support flange **18** is generally provided to facilitate the handling of containers, during formation and thereafter. Neck portion **16** further includes a tamper-evident formation **28** and a dispensing opening **24** positioned at, and formed by, the top of the neck portion **16**. In an embodiment, the dispensing opening has an inner diameter that is at least 22 mm. However, the dispensing opening may be of various conventional or non-conventional sizes and may, for example, comprise a circular opening having an inner diameter from 22 mm to 29 mm.

Container **10** is comprised of plastic. In an embodiment, the container may be comprised of polymer, such as a polymer that provides good visual clarity when bi-axially oriented like polyethylene terephthalate (PET). However, the invention is not limited to a specific polymer, and containers and preforms that are provided according to the teachings of the present invention may be comprised of a wide number of polymers and/or blends, including those that included recycled material.

The tamper-evident formation **28**, may be continuous or, as generally illustrated, may include one or more discontinuous formations. In an embodiment, the tamper-evident formation **28** is comprised of a discontinuous tamper bead. In other embodiments, the tamper-evident formation may comprise a formation (e.g., a lug or lugs) that extends from the upper and/or lower surface of the support ring. However, the invention is not limited to the illustrated means for indicating tampering and other means for indicating tampering, such as a covering (e.g., a foil covering) may be used instead of or in addition to other tamper-evident formations.

Embodiments of the container may additionally include a shoulder portion **15**, a plurality of threads **26** for comprising a closure (not shown). Shoulder portion **15** may comprise an upper portion of the sidewall portion **14**, and may extend inwardly into the neck portion **16**, although many container configurations do not include a shoulder portion. A feature of containers according to embodiments of the present

invention is a lowering of the center of gravity. For most configurations and applications, a lower center of gravity provides a container that is more stable and less likely to tip during manufacturing, processing, and/or handling. The center of gravity is the point at which if a body is suspended it would be perfectly balanced. For uniformly consistent, symmetrical bodies, the center of gravity is at the geometrical center. For non-consistent or non-symmetrical bodies, the center of gravity needs to be determined. Moreover, for purposes of the instant disclosure, the center of gravity is associated with preforms and with containers that are in an unfilled condition.

The center of gravity for container **10** illustrated in FIG. **1** is generally shown at **50**. It is noted that for the instant container configuration, the center of gravity **50** is above the mid-height of the container due to the additional material, and hence weight, that is provided in the container finish portion—i.e., the neck portion **16**. However, as described further herein, with a reduction in the vertical length and weight of the neck portion **16** (or elements thereof), the center of gravity for a container produced in accordance with the teachings of the present invention may have a center of gravity (e.g., **50**) that is vertically lower than that of a container that employs a conventional (vertically longer and heavier) neck portion. For example, without limitation, the ratio of the vertical height of the center of gravity to the vertical height of the container may be less than 0.57. Notably, for some embodiments the ratio may be less than 0.53.

Additionally, in an embodiment of the invention, portions of the container—exclusive of the neck portion—may be stretched (e.g., in a stretch blow molding operation) to more than 3 times their initial (i.e., preform component) length in the axial direction.

As one would also expect, with a reduction in the vertical length and weight of the neck portion, the center of gravity for an associated preform will also be reduced when compared to an preform of like material and design below the neck portion that includes a longer vertical and heavier neck portion.

FIGS. **2** and **3** generally illustrate a preform **40** according to an embodiment of the invention. Preform **40** can, for instance, be used to form a wide variety of containers, including a container such as that illustrated in FIG. **1**. By way of example, without limitation, preform **40** may be injection molded and/or blow molded, and may form an almost limitless number of container configurations. FIG. **4** depicts an enlarged portion of FIG. **2**.

Preform **40** is also shown including a neck portion **42**. For many applications, the neck portion provided in connection with a preform will remain substantially the same, and have substantially the same dimensions, as the neck portion of a molded container produced from the preform. Consequently, the neck portion **16** of the container **10** and the neck portion **42** of the preform may be substantially consistent, while the remaining portions of the preform and container—i.e., those below the respective neck portions—may change significantly. For ease of reference, common elements in the neck portion of the illustrated container and the neck portion of the illustrated preforms are provided with common reference numerals.

FIG. **5** illustrates a partial cross sectional view of an upper portion of a preform or a container formed from preform. In an embodiment, such as that generally illustrated, the vertical distance X from the top of the dispensing opening/neck portion (e.g., point **30**) to the lower surface **22** of the support flange **18** (e.g., point **32**) is 0.580 inches or less. For some

embodiments, X may be 0.500 inches or less; for other embodiments, vertical distance X may be less than 0.450 inches. FIG. **6** illustrates a perspective view of an upper/neck portion of a preform or a container **16**, **42** according to another embodiment. As illustrated in the figure, the neck may include threading of the type that is commonly employed in connection with containers for holding carbonated contents.

Moreover, as generally illustrated, the vertical distance H from the top of the dispensing opening/neck portion (e.g., point **30**) to the upper surface **20** of the support flange **18** may be 0.50 inches or less. For some embodiments, H may be 0.40 inches or less. Also, for some embodiments, the vertical distance D from the top of the dispensing opening/neck portion (e.g., point **30**) to the lower surface of the tamper-evident formation (e.g., point **34**) may be 0.30 inches or less.

In an embodiment, the vertical distance J from a furthest radially-extending portion of the lower surface of the tamper-evident formation **28** (e.g., point **36**) to the upper surface **20** of the support flange **18**, which generally equates to H minus D, may be 0.15 inches or less. For some embodiments, J may be 0.10 inches or less, and for other embodiments, vertical distance J may be less than 0.09 inches. For yet other embodiments, vertical distance J may be less than 0.08 inches.

Also, in an embodiment of the invention, the vertical distance between a furthest outwardly radially-extending portion of the lower surface of the tamper-evident formation (e.g., point **36**) to the lower surface **22** of the support flange **18** at the same outward radial distance—which may generally equate or coincide with X minus D—is 0.20 inches or less, and for some embodiments may be 0.15 inches or less.

In an embodiment, support flange **18** has a radially extending length L_1 that is 0.20 inches or less. For some applications, length L_1 may be further reduced to 0.17 inches or less. With further reference to support flange **18**, the angle—from horizontal—provided by a furthest outward radially extending portion of the lower surface **22** of support flange **18** (e.g., point **32**) to the nearest radially-extending portion of the upper surface **20** of the support flange **18** is 16° or greater, and may be $20.0^\circ \pm 2^\circ$. However, for some embodiments, such as that generally depicted in FIG. **5**, whereas a blending radius is provided to transition supporting flange **18** into an adjacent vertical portion of the neck (e.g., segment **39**), the nearest radially-extending portion of the upper surface **20** of support flange **18** may be a theoretical position within supporting flange **18**—e.g., point **38**. Furthermore, for some embodiment, the least distance from a furthest radially-extending portion of the support flange (e.g., point **32**) to the upper surface of the dispensing opening (e.g., at or about **30**) is 0.60 inches or less, and for some neck portions may be 0.50 inches or less.

Embodiments of preforms and containers may have a neck portion that weighs 3.0 grams or less. For some embodiments, the weight of the neck portion can be 2.3 grams or less. Further, for a 500 ml version of a container made in accordance with an embodiment of the invention, the total weight of the preform and an unfilled weight of a container produced from such a preform may be 11 grams or less, and for some embodiments may be 10 grams or less. Of course, for many embodiments, without limitation, the preform and resulting container will weigh at least 9 grams.

By providing a neck portion **16** for a container **10** that incorporates one or more aspects of the foregoing embodiments, the center of gravity (see, e.g., **50** in FIG. **1**) for the container may be lowered. For e.g., for a 500 ml container

5

of with a configuration as generally shown in FIG. 1, the weight of the neck portion may be reduced from a conventional 3.4 to 2.0 g. Based on such a reduction in weight, the center of gravity (see, e.g., 50) may become at least about 0.48 inches lower than that provided for a similarly configured container having a 3.4 g finish—and will likely be about 0.48 and 0.58 inches lower than with the heavier (e.g., 3.4 g) conventional finish. Providing a neck portion in accordance with embodiments disclosed herein for such a container can provide a lowering of center of gravity as a percentage of height from bottom that ranged from about 4.5% to about 6% when compared to a similar container with a conventional 3.4 g neck portion. Moreover, when a container such as that discussed in this paragraph (e.g., 2.0 g neck portion/finish) is compared to a conventional container (e.g. 3.4 g neck portion/finish), the calculations provide a drop or lowering in center of gravity that provides an approximately 10.5% to 12.2% relative percent change (i.e., percent improvement).

It is noted that in addition to the material and economic benefits that may be achieved by “light-weighting” and lowering a comparative center of gravity in a resultant container, a lowering in the center of gravity of a preform may also provide certain manufacturing benefits. For example, without limitation, a preform with a comparatively lower center of gravity may provide for improved sorting and/or handling during production and manufacturing. That is, among other things, a preform with a lower center of gravity can provide for comparatively more stable or improved retention and processing. Similarly, a container with a lower center of gravity may exhibit improved handling, for instance, without limitation, in connection with de-palletizing or with “table top” conveying systems. Further, a lower center of gravity can provide a container, filled or unfilled, with improved stability. It is further noted, however, that the present invention is not limited to containers that are blown and filled in distinct or separate operations. That is, without limitation, preforms and containers provided in accordance with the teachings of the present invention also lend themselves for use in connection with various conventional “blow-and-fill” operations, including those in which a container is filled just after formation (e.g., within seconds of formation) in close proximity to where the container is formed. The operation comprising the blow-and-fill may be a single, integrated machine, or may be comprised of two or more separate devices that are adjacent or in close proximity to one another.

The foregoing descriptions of specific embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, and various modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to explain the principles of the invention and its practical application, to thereby enable others skilled in the art to utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the claims appended hereto and their equivalents.

What is claimed is:

1. A container assembly, comprising:

- (i) a plastic blow molded container comprising:
 - a lower supporting base portion;
 - a sidewall portion extending upwardly from the base portion; and

6

a neck portion extending upwardly from the sidewall portion, the neck portion including a dispensing opening positioned at a top of the neck portion, the dispensing opening having a top; threads positioned below the dispensing opening, a tamper-evident formation positioned below the threads, the tamper-evident formation having a lower surface, and a support flange positioned below the tamper-evident formation, the support flange having an upper surface and a lower surface; and

(ii) a closure configured to receive the threads;

wherein the container is formed of a material comprising polyethylene terephthalate (PET); a weight of the neck portion from the lower surface of the support flange to a top of the dispensing opening is 2.3 grams or less; an outside diameter of the support flange is greater than 22 mm and less than or equal to 39.2 mm; and a volume of the container is at least 500 ml.

2. The container assembly according to claim 1, wherein a vertical distance from the top of the dispensing opening to the lower surface of the support flange is 0.580 inches or less.

3. The container assembly according to claim 1, wherein a vertical distance from the top of the dispensing opening to the lower surface of the support flange is 0.500 inches or less.

4. The container assembly according to claim 1, wherein a vertical distance from the top of the dispensing opening to the lower surface of the support flange is 0.450 inches or less.

5. The container assembly according to claim 1, wherein a vertical distance from a lower surface of the tamper-evident formation to the top of the dispensing opening is 0.30 inches or less.

6. The container assembly according to claim 1, wherein a vertical distance from the top of the dispensing opening to the upper surface of the support flange is 0.50 inches or less.

7. The container assembly according to claim 1, wherein a vertical distance from the top of the dispensing opening to the upper surface of the support flange is 0.40 inches or less.

8. The container assembly according to claim 1, wherein a vertical distance from a furthest outwardly radially-extending portion of a lower surface of the tamper-evident formation to the upper surface of the support flange at the same outward radial distance is 0.10 inches or less.

9. The container assembly according to claim 1, wherein an inner diameter of the dispensing opening is between 22 mm and 29 mm.

10. The container assembly according to claim 1, wherein the tamper-evident formation comprises a bead.

11. The container assembly according to claim 1, wherein a vertical distance from a furthest outwardly radially-extending portion of a lower surface of the tamper-evident formation to the lower surface of the support flange at the same outward radial distance is 0.20 inches or less.

12. The container assembly according to claim 1, wherein a combined weight of the lower supporting base portion, the sidewall portion and the neck portion is 11 grams or less.

13. The container assembly according to claim 1, wherein a combined weight of the lower supporting base portion, the sidewall portion and the neck portion is 10 grams or less.

14. The container assembly according to claim 1, wherein the threads comprise multiple-lead threads.

15. The container assembly according to claim 1, wherein a vertical distance from a furthest outwardly radially-extending portion of a lower surface of the tamper-evident formation to the upper surface of the support flange at the same outward radial distance is 0.10 inches or less.

16. The container assembly according to claim 1, wherein a radially extending length of the support flange is 0.17 inches or less.

17. A container assembly, comprising:

(i) a plastic blow molded container comprising:

a lower supporting base portion;

a sidewall portion extending upwardly from the base portion; and

a neck portion extending upwardly from the sidewall portion, the neck portion including a dispensing opening positioned at a top of the neck portion, the dispensing opening having a top; threads positioned below the dispensing opening; a tamper-evident formation positioned below the threads, the tamper-evident formation having a lower surface; and a support flange positioned below the tamper-evident formation, the support flange having an upper surface and a lower surface; and

(ii) a closure configured to receive the threads;

wherein the container is formed of a material comprising polyethylene terephthalate (PET); a weight of the neck portion from the lower surface of the support flange to a top of the dispensing opening is 2.3 grams or less; a combined weight of the lower supporting base portion, the sidewall portion and the neck portion is 11 grams or less; and a volume of the container is at least 500 ml.

18. The container assembly according to claim 17, wherein a vertical distance from the top of the dispensing opening to the lower surface of the support flange is 0.580 inches or less.

19. The container assembly according to claim 17, wherein a vertical distance from the top of the dispensing opening to the lower surface of the support flange is 0.500 inches or less.

20. The container assembly according to claim 17, wherein a vertical distance from the top of the dispensing opening to the lower surface of the support flange is 0.450 inches or less.

21. The container assembly according to claim 17, wherein a vertical distance from a lower surface of the tamper-evident formation to the top of the dispensing opening is 0.30 inches or less.

22. The container assembly according to claim 17, wherein a vertical distance from the top of the dispensing opening to the upper surface of the support flange is 0.50 inches or less.

23. The container assembly according to claim 17, wherein a vertical distance from the top of the dispensing opening to the upper surface of the support flange is 0.40 inches or less.

24. The container assembly according to claim 17, wherein a vertical distance from a furthest outwardly radially-extending portion of a lower surface of the tamper-evident formation to the upper surface of the support flange at the same outward radial distance is 0.10 inches or less.

25. The container assembly according to claim 17, wherein an inner diameter of the dispensing opening is between 22 mm and 29 mm.

26. The container assembly according to claim 17, wherein a vertical distance from a furthest outwardly radially-extending portion of a lower surface of the tamper-evident formation to the lower surface of the support flange at the same outward radial distance is 0.20 inches or less.

27. The container assembly according to claim 17, wherein a combined weight of the lower supporting base portion, the sidewall portion and the neck portion is 10 grams or less.

28. The container assembly according to claim 17, wherein a vertical distance from a furthest outwardly radially-extending portion of a lower surface of the tamper-evident formation to the upper surface of the support flange at the same outward radial distance is 0.10 inches or less.

29. The container assembly according to claim 17, wherein a radially extending length of the support flange is 0.17 inches or less.

30. The container assembly according to claim 17, wherein the container is filled with a beverage.

* * * * *